

Product Safety Data Sheet

XEROX

Product: 5201, 5203, 5305, 5306, XC351, XC355, XC356

PSDS No.: 0723

ISSUE DATE: 11/25/94

REV. DATE: 11/12/98

Section I - Product Identification

Manufacturer's Name

Xerox Corporation

Manufacturer's Address

Rochester, New York 14644

Product Designation

5201, 5203, 5305, 5306, XC351, XC355, XC356

Emergency No.

(585) 422-2177

EH&S Inquiries

(800) 828-6571

Product Identifier

US: 3GD, 6GD, 9GD, 2GE

Canada: 3GD, 6GD, 9GD, 2GE

L4K, L5K, L6K

Section II - Electrical Information

Line Voltage

(Volts)

120

Line Current

(Amps)

6.0

Freq.

(Hertz)

80

Branch Cir. Protection

(Amps)

15

Line Cord/Plug Specification

Single Phase 2 wire & Ground

NEMA 5-15P

Agency Approval

UL File Number E145607, E24014(M)

CSA LR Number LR35136

Power Consumption(Watts)*

Running: 144.0

Standby: 30.7

Section III - Supplies

Dry Ink

Xerox Part No.

6R735

Material Safety Data Sheet

A-0198

Section IV - Environmental Information

Product Size

Configuration (Centimeters / Inches)

D: 35 / 13.8

W: 36 / 14.2

H: 10 / 3.9

Heat Emission*

(BTU/HR)

Running: 492

Standby: 105

Environmental Limitations

Relative Humidity (%)

Ambient Temp. (°C)

Min Max

15 85

10 32

Floor Space Requirements

(Meters / Feet)

75(W) x 43(D) / 2 x 1

Weight

(K Grams / Lbs.)

6 / 13

* Based on a five minute average

Section V - Emission/Exposure Information*

Light Source

Tungsten Lamp Array, 32 Watts

Electromagnetic Emissions

US FCC: Class B

Canada DOC: Class B

Audible Noise

Run 43.0 dB(A)

Standby 30.5 dB(A)

Impulse 54.2 dB(A)

TLV

85.0 dB(A)

Ozone

Concentration Based on Simulation Model:

Daily Copy Volume 45 copies/7.96 hours

Room Size 5.83 m³

1/2 Air Room Change per Hour

Ozone Filter - None

98.13 ug/min

0.002 ppm (TWA)

0.004 ppm (STEL)

TLV

0.1 ppm

Total Dust

0.009 mg/m³

TLV

10 mg/m³

* **TLV** (Threshold Limit Value) and **PEL** (Permissible Exposure Level) respectively set by American Conference of Government Industrial Hygienists and by Occupational Safety and Health Administration. These levels are considered maximum exposure permitted to ensure no health hazard. **TWA** (Time Weighted Average) for a normal eight-hour workday. **STEL** (Short Term Exposure Level).

11/12/98

All measurements were made on products performing within established operating specifications and received recommended maintenance procedures. Xerox certifies that this product meets or exceeds the applicable standards for safety and emissions.