



# ISO/IEC 19752 Yield Test Report



## Phaser 4500 Toner Cartridge (Standard Capacity)

Declaration of Yield:

**Published Cartridge Yield: 10,000 standard pages**  
**Declared yield value in accordance with ISO/IEC 19752**

Average: 10,313  
 Standard Deviation: 365  
 90% Lower Confidence: 10,087

### "Customer Report, compliant with ISO/IEC 29142"

	<u>Start</u>	<u>End</u>
<b>Date Tested:</b>	18-May-2007	1-Jun-2007
Number of Cartridges used in testing:	9	
Number of Cartridges used in calculations:	9	
Type of Cartridge:	Standard Capacity Cartridge	
Shake Procedure Used?	yes	
Print mode:	Continuous (500pages/job)	
Number of engines used in testing:	3	
Media Used:	Xerox 4200	
Paper Weight:	20lb	
Paper Size:	A4	
Paper feed orientation:	Long Edge Feed (LEF)	
Computer Model:	Dell PC 1.2GHz	
Driver Version:	Xerox	
Operating System:	Windows XP	
Application Software:	Adobe Acrobat Professional 7.0.1	
Test Page Version:	ISO/IEC 19752:2004	
Power (off/on) everyday?	No	

Cartridge Serial Number	Printer Serial Number	Temperature (°C)			Humidity (%RH)			Cartridge Yield	Included in calc.
		Avg.	Max	Min	Avg.	Max	Min		
CN-084K-10799-71R 2000000131	XWO3541	22.6	25.0	22.0	50.0	51.0	50.0	10,215	y
CN-084K-10799-71R 2000000108	XWO3541	22.5	22.8	22.3	50.0	51.0	49.0	10,640	y
CN-084K-10799-71R 2000000135	XWO3541	22.6	22.8	22.4	50.0	51.0	50.0	10,303	y
CN-084K-10799-71R 2000000119	XW03751	22.5	22.8	22.0	50.0	50.0	50.0	10,482	y
CN-084K-10799-71R 2000000146	XW03751	22.7	22.8	22.5	50.0	50.0	50.0	10,625	y
CN-084K-10799-71R 2000000147	XW03751	22.6	22.8	22.4	50.0	50.0	50.0	10,131	y
CN-084K-10799-71R 2000000137	XW03613	22.5	22.8	22.0	50.0	50.0	49.0	10,457	y
CN-084K-10799-71R 2000000138	XW03613	22.7	22.8	22.5	50.0	51.0	49.0	10,504	y
CN-084K-10799-71R 2000000139	XW03613	22.6	22.8	22.4	50.0	51.0	50.0	9,458	y

Comments: